

Ensemble Tuyau Standard PUX + Joint Standard



| DN | Classe | Déviation angulaire | PFA | Référence |
|------|--------|---------------------|--------|----------------|
| 150 | C40 | 5 ° | 40 bar | SSB15Q60AH-E00 |
| 200 | C40 | 5 ° | 40 bar | SSB20Q60AH-E00 |
| 250 | C40 | 5 ° | 40 bar | SSB25Q60AH-E00 |
| 250 | C50 | 5 ° | 50 bar | SSB25D60AH-E00 |
| 300 | C40 | 5 ° | 40 bar | SSB30F60AH-E00 |
| 350 | C30 | 4 ° | 30 bar | SSB35G60AH-E00 |
| 400 | C30 | 4 ° | 30 bar | SSB40G60AH-E00 |
| 450 | C30 | 4 ° | 30 bar | SSB45G60AH-E00 |
| 500 | C30 | 4 ° | 30 bar | SSB50G60AH-E00 |
| 500 | C40 | 4 ° | 40 bar | SSB50F60AH-E00 |
| 600 | C30 | 4 ° | 30 bar | SSB60G60AH-E00 |
| 700 | C25 | 4 ° | 25 bar | SSB70H70AH-E00 |
| 800 | C25 | 4 ° | 25 bar | SSB80H70AH-E00 |
| 900 | C25 | 4 ° | 25 bar | SSB90H70AH-E00 |
| 1000 | C25 | 4 ° | 25 bar | SSC10H70AH-E00 |
| 1100 | C25 | 4 ° | 25 bar | SSC11H80AH-E00 |
| 1200 | C25 | 4 ° | 25 bar | SSC12H80AH-E00 |
| 1400 | C25 | 3 ° | 25 bar | SSC14H80AH-E00 |
| 1500 | C25 | 3 ° | 25 bar | SSC15H80AH-E00 |
| 1600 | C25 | 3 ° | 25 bar | SSC16H80AH-E00 |
| 1800 | C25 | 2,5 ° | 25 bar | SSC18H80AH-E00 |
| 2000 | C25 | 2 ° | 25 bar | SSC20H80AH-E00 |

(*) merci de nous contacter

Produits associés



Bague de joint Standard
pour Tuyaux et Raccords
DN60-2000