


Ductile iron Adapter Gravity to 1 socket for Iron and 1 spigot-end for PVC + 1 STD G gasket



To ensure the connection between a socket of ductile iron pipe / a spigot end for PVC.

DN (mm)	ØDE1 DI (mm)	ØDE2 PVC (mm)	P1 DI (mm)	P2 PVC (mm)	Lu (mm)	Lt (mm)	Mass (kg)	References
150x160	169,7	160	94	100	56	250	7.50	TUB15MB0JS
200x200	221,6	200	100	100	50	250	10.60	TUB20MB0KS

Field of use:

- Separate sewer system
- Application: gravity flow
- Type of effluent: wastewater
- Lastingly leak tight and impermeable
- Laying in all types of soils
- For effluents between pH1 and pH13

Main characteristics:

- External and internal coating: red epoxy powder 250µm (PECR)
- STANDARD G Gasket (STD G) in Nitrile
- Fittings and joints are supplied in red-brown polyethylene bag
- EN 598 / CE Marking
- Declaration of performances [DoP-BIOGAN002EN](#)

- Designed according to the regulatory texts:
 - NF EN 476: general prescriptions for components used in the networks
 - NF EN 752: Conception of sewage projects
 - NF EN 1610: Reception of the works
 - CCTG: Fascicule 70 (sewage work)

Linked products



Standard G Gasket (STD G)
for BIOGAN pipes and
fittings DN150-200

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.