



67°30' Angle Branch (all spigot) DN150-300



DN (mm)	ØDE maxi coated (mm)	P (mm)	Lt (mm)	Lu (mm)	Ødn (mm)	Øde (mm)	p (mm)	Hu (mm)	Mass (kg)	References
150	171.5	113	493	267	125	145.5	120	270	17.40	TUB15TF0G
200	223.5	124	568	320	125	145.5	120	310	25.80	TUB20TF0G
200	223.5	124	568	320	150	171.5	120	310	26.20	TUB20TF0J

Field of use:

- Separate sewer system
- Application: gravity flow
- Type of effluent: wastewater
- Lastingly leak tight and impermeable
- Laying in all types of soils
- For effluents between pH1 and pH13

Main characteristics:

- External and internal coating: red epoxy powder 250µm (PECR)
- IM Gasket in Nitrile
- Fittings and joints are supplied in red-brown polyethylene bag
- EN 598 / CE Marking
- Declaration of performances [DoP-BIOGAN002EN](#)
- Designed according to the regulatory texts:
 - NF EN 476: general prescriptions for components used in the networks
 - NF EN 752: Conception of sewage projects
 - NF EN 1610: Reception of the works
 - CCTG: Fascicule 70 (sewage work)

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.