


PVC Connecting Piece (1 spigot for ductile iron and 1 spigot for PVC) DN125-200



DN (mm)	Lt (mm)	ØDe1 maxi for ductile iron spigot (mm)	P1 (mm)	ØDE for PVC spigot (mm)	ØDE2 maxi (mm)	P2 (mm)	Mass (kg)	References
125	200	145.5	90	125	125.4	89	4.50	TUB12NBOG
150	200	171.5	90	160	161	89	5.80	TUB15NBOX
200	200	223.5	90	200	201	89	7.20	TUB20NBOK

Field of use:

- Separate sewer system
- Application: gravity flow
- Type of effluent: wastewater
- Lastingly leak tight and impermeable
- Laying in all types of soils
- For effluents between pH1 and pH13

Main characteristics:

- External and internal coating: red epoxy powder 250µm (PECR)
- IM Gasket in Nitrile
- Fittings and joints are supplied in red-brown polyethylene bag
- EN 598 / CE Marking
- Declaration of performances [DoP-BIOGAN002EN](#)
- Designed according to the regulatory texts:
 - NF EN 476: general prescriptions for components used in the networks
 - NF EN 752: Conception of sewage projects

- NF EN 1610: Reception of the works
- CCTG: Fascicule 70 (sewage work)

Linked products



IM Seal for gravity fittings

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.