


## Asymmetrical coupling



Junction ductile iron DN150 with ductile iron DN125

DN (mm)	ØDI (mm)	Ødi (mm)	P (mm)	p (mm)	Mass (kg)	References
150x125	173	158.2	101	80	4.60	TJB12MW0J

### Field of use:

- Separate sewer system
- Application: gravity flow
- Type of effluent: wastewater
- Lastingly leak tight and impermeable
- Laying in all types of soils
- For effluents between pH1 and pH13

### Main characteristics:

- External and internal coating: red epoxy powder 250µm (PECR)
- IM Gasket in Nitrile
- Fittings and joints are supplied in red-brown polyethylene bag
- EN 598 / CE Marking
- Declaration of performances [DoP-BIOGAN002EN](#)
- Designed according to the regulatory texts:
  - NF EN 476: general prescriptions for components used in the networks
  - NF EN 752: Conception of sewage projects
  - NF EN 1610: Reception of the works

- CCTG: Fascicule 70 (sewage work)
- Supermetic Seal in SBR rubber

## Linked products



IM Seal for gravity fittings

*The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.*