


Bend 45° (1/8) INTEGRAL with 2 sockets STANDARD



Angle	DN (mm)	Lu (mm)	P (mm)	ØDI (mm)	ØB (mm)	Mass (kg)	References
45°	1100	540	190	1155	1300	980.00	SSC11CB00FF
45°	1200	537.5	195	1263	1412.5	1015.00	SSC12CB00FF
45°	1400	522	255	1467	1600	1555.00	SSC14CB00FF
45°	1500	572	280	1570	1742	1815.00	SSC15CB00FF
45°	1600	563	275	1673	1820	2089.00	SSC16CB00FF
45°	1800	642	258	1881.7	2038.2	3126.00	SSC18CB00FF
45°	2000	685	290	2089	2269	3702.00	SSC20CB00FF

Field of use:


- Separate sewer system and combined sewer system
- Application: gravity flow and rising main sewerage systems
- Type of effluent: domestic wastewater and rainwater
- For networks with rising main under pressure
- For effluents between pH1 and pH13

Main characteristics:


- External and internal coating: red epoxy powder 250µm (PECR)
- Type of joint: Standard
- Standard Gasket in Nitrile
- EN 598 / CE Marking
- Declaration of performances [DoP-INTEGRAL005EN](#)
- Mark NF

- Designed according to the regulatory texts:
 - NF EN 476: general prescriptions for components used in the networks
 - NF EN 752: Conception of sewage projects
 - NF EN 1610: Reception of the works
 - CCTG: Fascicule 70 (sewage work)

Linked products



Nitrile STD Gasket
DN80-2000



STD Ve joint for INTEGRAL
STD Fittings

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.