


Kit Standard PUX Pipe + Standard Gasket



DN	Class	Angular deflection	PFA	References
150	C40	5 °	40 bar	SSB15Q60AH-E00
200	C40	5 °	40 bar	SSB20Q60AH-E00
250	C40	5 °	40 bar	SSB25Q60AH-E00
250	C50	5 °	50 bar	SSB25D60AH-E00
300	C40	5 °	40 bar	SSB30F60AH-E00
350	C30	4 °	30 bar	SSB35G60AH-E00
400	C30	4 °	30 bar	SSB40G60AH-E00
450	C30	4 °	30 bar	SSB45G60AH-E00
500	C30	4 °	30 bar	SSB50G60AH-E00
500	C40	4 °	40 bar	SSB50F60AH-E00
600	C30	4 °	30 bar	SSB60G60AH-E00
700	C25	4 °	25 bar	SSB70H70AH-E00
800	C25	4 °	25 bar	SSB80H70AH-E00
900	C25	4 °	25 bar	SSB90H70AH-E00
1000	C25	4 °	25 bar	SSC10H70AH-E00
1100	C25	4 °	25 bar	SSC11H80AH-E00
1200	C25	4 °	25 bar	SSC12H80AH-E00
1400	C25	3 °	25 bar	SSC14H80AH-E00
1500	C25	3 °	25 bar	SSC15H80AH-E00
1600	C25	3 °	25 bar	SSC16H80AH-E00
1800	C25	2.5 °	25 bar	SSC18H80AH-E00
2000	C25	2 °	25 bar	SSC20H80AH-E00

(*) consult us

Linked products



Standard gasket for Pipes
and Fittings DN60-2000

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.