


SELECTA 500 Gully unit A profile - Grating with selector bar - C250 class



| AxB (mm) | C (mm) | D (mm) | E (mm) | H (mm) | h1 (mm) | h2 (mm) | Grating mass (kg) | Cover mass (kg) | Mass of frame + extension (kg) | Total mass (kg) | Waterway area | Packaging | References |
|----------|--------|--------|--------|--------|---------|---------|-------------------|-----------------|--------------------------------|-----------------|---------------------|-----------|------------|
| 570x610 | 250 | 229 | 273 | 125 | 90 | 65 | 16.5 | 13 | 21 | 50.50 | 7.6 dm ² | 10 | ECSE61SF |



Material and coating:

- Frame, grating and cover in Ductile Iron EN GJS 400-15: water base

Origine France Garantie

- This product is made in France in our foundry in Blénod-les-Pont-A-Mousson (54), and is certified Origine France Garantie. This guarantees consumers that the product is made in France in accordance with specifications available on originefrancegarantie.fr. The certification number is: BVCert 6026906.
- *"Origine France Garantie certification is awarded by an independent certification body. Checks are then carried out every year to ensure that the product is indeed 100% made in France and that at least 50% of the product's manufacturing costs (including raw materials) are of French origin".*

Field of application:

- C250 class (Group 3) according to standard EN 124-2, destined to the circulated pavements and similar locations exposed to the access of vehicles.
- Compatible with the A1 and A2 kerbs and CS2, CS3 and CS4 gutters according standard to NF P 98-340.

Main characteristics:

- Grating and cover:
 - Hinged separately and can be easily dismantled
 - Secured by spring-bar lock requiring a tool for the opening.
- Grating:
 - With raised selector bar allowing the screening of debris
 - Optimized design for absorption and safety.
- Clear opening Ø 385 mm.
- [Implementation](#)

Linked products



Gully units SELECTA 500
and MAXI C250 -
Implementation



The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.