

Kit Universal Standard Ve INTEGRAL Pipe + Universal Standard Ve Joint




DN	Angular deflection	PFA	References
150	3 °	60 bar	TFB15N60BP-E02
200	3 °	52 bar	TFB20N60BP-E02
250	3 °	46 bar	TFB25N60BP-E02
300	3 °	41 bar	TFB30N60BP-E02
350	3 °	38 bar	TFB35N60BP-E02
400	3 °	35 bar	TFB40N60BP-E02
450	3 °	32 bar	TFB45N60BP-E02
500	3 °	30 bar	TFB50N60BP-E02
600	2 °	30 bar	TFB60N60BP-E02
700	2 °	27 bar	TFB70N70BP-E02
800	2 °	25 bar	TFB80N70BP-E02
900	1.5 °	25 bar	TFB90N70BP-E02
1000	1.2 °	25 bar	TFC10N70BP-E02
1200	1.1 °	20 bar	TFC12N80BP-E02
1400	1.2 °	16 bar	TFC14N80BP-E02
1600	0.9 °	16 bar	TFC16N80BP-E02

Accessories



Assembling and disassembling wedges for Universal Ve Joint

Linked products



UNI STD Ve joint for INTEGRAL® Pipes and Fittings DN100-1600

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.