


Taper INTEGRAL with 2 sockets STANDARD



DN (mm)	Ødn (mm)	Lu (mm)	P (mm)	ØDI (mm)	ØB (mm)	p (mm)	Ødi (mm)	Mass (kg)	References
700	500	480	150	742.2	861	120	535	198.00	SSB70VE0QFF
700	600	267.5	150	742.2	861	120	638	176.00	TSB70VE0R
800	600	467.5	160	846.3	972	120	638	255.00	TSB80VE0R
800	700	280	160	846.3	972	150	742.2	243.00	TSB80VE0S
900	700	480	175	949.4	1080	150	742.2	338.00	SSB90VE0SFF
900	800	280	175	949.4	1080	160	846.3	282.00	SSB90VE0TFF
1000	800	480	185	1052.5	1189	160	846.3	417.00	SSC10VE0TFF
1000	900	280	185	1052.5	1189	175	949.4	378.00	SSC10VE0UFF
1200	1000	480	195	1263	1412	185	1052.5	543.00	SSC12VE0VFF
1400	1200	360	255	1467	1600	195	1263	714.00	SSC14VE0BFF
1500	1200	410	280	1570	1742	195	1263	824.00	SSC15VE0BFF
1600	1200	645	275	1673	1820	195	1263	1065.00	SSC16VE0BFF
1600	1400	350	275	1673	1820	255	1467	1009.00	SSC16VE0CFF
1800	1600	427	258	1881.7	2038	275	1673	1267.00	SSC18VE0EFF


Field of use:

- Separate sewer system and combined sewer system
- Application: gravity flow and rising main sewerage systems
- Type of effluent: domestic wastewater and rainwater
- For networks with rising main under pressure
- For effluents between pH1 and pH13


Main characteristics:

- External and internal coating: red epoxy powder 250µm (PECR)
- Type of joint: Standard
- Standard Gasket in Nitrile
- EN 598 / CE Marking
- Declaration of performances [DoP-INTEGRAL005EN](#)
- Mark NF
- Designed according to the regulatory texts:
 - NF EN 476: general prescriptions for components used in the networks
 - NF EN 752: Conception of sewage projects
 - NF EN 1610: Reception of the works
 - CCTG: Fascicule 70 (sewage work)


Linked products



Nitrile STD Gasket
DN80-2000



Gasket ViLoK® (NBR STD
Vi) DN80-700



STD Ve joint for INTEGRAL
STD Fittings

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.