

## Lubricating paste - BLUPAM



Gel-based lubricant for assembling pipes, collars, and fittings in pressure and sewerage systems. Available in 500g, 800g, and 2.5kg packages.

| Version | Mass    | References |
|---------|---------|------------|
| Pot     | 0.50 kg | 289625     |
| Pot     | 0.80 kg | 289624     |
| Pot     | 2.50 kg | 289626     |

### Scope of application

Suitable for coated cast iron, PVC, PVC-O, PE, PP, GRP, and concrete. Not suitable for ABS.


### Properties and technical specifications

Color: Transparent light blue / Density approx.: 1 g/cm<sup>3</sup> / Raw material: Water-soluble polymer  
Acid-free / Thixotropic / Water-soluble

### Quality labels and health compliance

- CLP: Complies with the reference positive lists.
- Hydrocheck: Complies with the requirements of the aggregation procedure - Approved by BELGAQUA
- WRAS: Meets the requirements of BS6920-1:2000 and/or 2014

## Implementation and instructions for use



Apply a sufficient amount of lubricating paste with a brush.

1. Clean the ends, the joint ring, and its housing.
2. Install the joint according to the installation instructions.
3. Coat the entire exposed surface of the joint ring.
4. Coat the chamfer and the spigot of the pipe. (See quantity table). **Do not lubricate the inside of the joint groove.**
5. Assemble immediately, centering the joint to be fitted and following the installation instructions for drinking water and sewerage networks.

*Do not install at temperatures below -5°C. / Clean with water.*

*Follow the usage recommendations in the safety data sheets available in the Documentation Area at [www.pamline.com](http://www.pamline.com).*

### Quantitative indications:

| DN                              | 60  | 80  | 100 | 125 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 600 | 700 | 800 | 900 | 1000 |
|---------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| Quantity of joints / pot 500 gr | 89  | 65  | 51  | 39  | 32  | 22  | 18  | 15  | 12  | 11  | 9   | 8   | 6   | 4   | 3   | 3   | 2    |
| Quantity of joints / pot 800 gr | 142 | 103 | 81  | 63  | 51  | 36  | 29  | 24  | 20  | 17  | 15  | 13  | 10  | 6   | 5   | 4   | 4    |
| Quantity of joints / pot 2,5 kg | 445 | 323 | 253 | 196 | 158 | 112 | 91  | 74  | 62  | 53  | 46  | 41  | 30  | 18  | 15  | 13  | 12   |

### Storage and disposal conditions

Shelf life: 12 months after opening – Reseal immediately after use – Store away from light and in a dry place at a temperature between +5°C and +25°C. The best-before date is indicated on the packaging.

Do not pour into drains, onto the ground, or into waterways. The waste code does not relate to the product itself but to its application. The waste code must be assigned by the user, depending on the product's application.

*Our advice is based on laboratory tests and practical experience. Due to the wide variety of materials and/or conditions of use of our products, we cannot accept any liability for the results obtained and/or for any damage resulting from the use of the product. However, we are at your disposal to offer you advice.*

*The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.*