


Bend 45° (1/8) NATURAL with 2 sockets STANDARD



Angle	DN (mm)	Lu (mm)	P (mm)	ØDI (mm)	ØB (mm)	Mass (kg)	References
45°	60	76	82	80.2	143.5	6.50	NSA60CB00NN2
45°	80	56.5	85	101.4	167.5	7.00	NSA80CB00NN2
45°	100	65	88	121.4	187.5	8.90	NSB10CB00NN2
45°	125	83.5	91	147.4	214.5	12.30	NSB12CB00NN2
45°	150	92.5	94	173.4	241	15.60	NSB15CB00NN2
45°	200	100	100	225.5	294	23.70	NSB20CB00NN2
45°	250	136	105	277.3	351	40.50	NSB25CB00NN2
45°	300	167.5	110	329.3	408.3	59.00	NSB30CB00NN2

Field of use:

- For drinking water networks
- The scope of use of Aquacoat® fittings in soils is equivalent to that of Natural Biozinalium® pipes, it is suitable for the majority of soils, as defined in appendix D.2.2 of standard EN545:2010. exception :
 - peaty and acidic soils
 - soils containing waste, ashes, slag or contaminated by certain waste or industrial effluents
 - soils located below the level of the marine water table having a resistivity less than 500 Ω cm
- In such soils, or in other aggressive environments, or in the event of stray currents, it is recommended to use other, more suitable types of coatings.

Main characteristics:

- Inside-Outside coating: Aquacoat fittings (AQB) without Bisphenol
- In conformity with EN 545:2010 and ISO 2531:2009

Linked products



Kit Standard Bend AQB +
Standard Gasket



Kit Standard Fitting AQB +
Standard Vi Gasket



Kit Standard Fitting AQB +
Standard Ve Joint

The information on this sketch is, to the best of our knowledge correct at the time of printing. However Saint-Gobain are constantly looking at ways of improving their products and services therefore reserve the right to change without prior notice, any of the data shown. Any orders placed will be subject to our Standard Conditions of Sale, available on request.